


# Mutual authentication / cipher key delivery system

Bibliographic data	Description	Claims	Mosaics	Original document	INPADOC legal status
<b>Publication number:</b>	GB2279540 (A)				<b>Also published as:</b>
<b>Publication date:</b>	1995-01-04				GB2279540 (B)
<b>Inventor(s):</b>	TSUBAKIYAMA HIDEKI				US5544245 (A)
<b>Applicant(s):</b>	KOKUSAI DENSHIN DENWA CO LTD [JP]				JP6350598 (A)
<b>Classification:</b>					
- international:	G09C1/00; H04L9/06; H04L9/08; H04L9/14; H04L9/32; H04L12/22; G09C1/00; H04L9/06; H04L9/08; H04L9/14; H04L9/32; H04L12/22; (IPC1-7): H04L9/32				
- European:	H04L9/32B				
<b>Application number:</b>	GB19940011680 19940610				
<b>Priority number(s):</b>	JP19930163898 19930610				
View INPADOC patent family					
View list of citing documents					

## Abstract of GB 2279540 (A)

A network and each user  $i$  share an encryption algorithm  $E_{K_i}()$  using his authentication key  $K_i$  as a cipher key, its inverse function  $E_{K_i}^{-1}()$ , a specific function  $F()$  and its inverse function  $F^{-1}()$ , and a function  $G()$ . The network calculates  $C1 = E_{K_i}(F(r_n, r_u))$ , using a random number  $r_n$  generated by the user and a random number  $r_u$  generated by the network, and sends it to the user. The user calculates  $(d1, d2) = F^{-1}(E_{K_i}^{-1}(C1))$  and, if  $d1 = r_n$ , judges the network to be an authorized one. The user generates a random number  $r_c$  and sends  $C2 = E_{K_i}(F(d2, r_c))$  to the network. The network calculates  $(d3, d4) = F^{-1}(E_{K_i}^{-1}(C2))$  and, if  $d3 = r_u$ , judges the user to be an authorized one.

Fig. 1



$ID_i$ : IDENTIFIER OF USER NAMED  $i$   
 $r_u$ : RANDOM NUMBER GENERATED BY NETWORK  
 $r_n$ : RANDOM NUMBER GENERATED BY USER  
 $r_c$ : RANDOM NUMBER GENERATED BY USER  
 $K_i$ : AUTHENTICATION KEY OF USER NAMED  $i$   
 $E_{K_i}()$ : ENCRYPTION FUNCTION OF A COMMON-KEY CRYPTOSYSTEM USING CRYPTOGRAPHIC-KEY  $K_i$   
 $F()$ : DATA COMBINER FOR SATISFYING [CONDITIONS FOR FUNCTION  $F()$ ]